Epson Stylus Photo R2000 Printer Specifications

Printing Technology

Advanced MicroPiezo AMC print head with ink-repelling coating technology

8-channel, drop-on-demand, ink jet print head

Ink Type

Epson UltraChrome Hi-Gloss 2 pigment ink 8-color (C, M, Y, PK, MK, R, OR and GO)

Nozzle Configuration

Color and Monochrome heads 180 nozzles x 8

Droplet Technology

Smallest droplet size 1.5 picoliters
Variable Droplet Technology can produce up to three different droplet sizes per print line

Maximum Resolution

5760 x 1440 optimized dpi

Printer Speed^A

8" x 10" print Approx. 1 min 8 sec 11" x 14" print Approx. 1 min 43 sec

Paper Types

Supports plain paper, Epson Bright White Paper, Presentation Paper Matte, Premium Presentation Paper Matte, Premium Presentation Paper Matte, Premium Presentation Paper Matte Double-sided, Ultra Premium Presentation Paper Matte, Photo Paper Glossy, Premium Photo Paper Glossy, Ultra Premium Photo Paper Glossy, Premium Photo Paper Semi-gloss, Ultra Premium Photo Paper Luster, Watercolor Paper Radiant White, Velvet Fine Art Paper, UltraSmooth® Fine Art Paper, Hot Press Natural, Hot Press Bright, Cold Press Natural, Cold Press Bright, Exhibition Canvas Matte, Exhibition Canvas Satin, Exhibition Canvas Gloss, Scrapbook Photo Paper Matte Double-sided and ink jet printable CD/DVDs

Printable Area

Maximum paper width13"Maximum cut-sheet size13" x 19"Minimum cut-sheet size3.5" x 5"Maximum printable area13" x 44"

BorderFree Print Sizes

3.5" x 5", 4" x 6", 5" x 7", 8" x 10", A4 (8.3" x 11.7"), letter (8.5" x 11"), 11" x 14", 12" x 12", A3 (11.7" x 16.5") and Super B (13" x 19") sizes

Media Handling

Auto sheet feeder

Up to 13" x 19"
Up to 120 sheets plain; 30 photo

Manual rear path
Single sheet manual feeder,
designed for fine art paper

Roll paper
8.3" and 13" rolls

Front media path
Up to 13" x 19"

Single sheet manual feeder, designed for media up to 1.3 mm thick, 1 CD/DVD (using included tray)

Epson Intelligent Ink Cartridges

Ink cartridge shelf life 3 years from printed production date or 6 months after opened

Environmental Characteristics

Temperature
Operating 50 * to 95 *F (10 * to 35 *C)
Storage -4 * to 104 *F (-20 * to 40 *C)
Relative humidity
Operating 20 to 80% (no condensation)
Recommended storage 5 to 85% (no condensation)

Safety Approvals

Safety standards

UL1950, CSA 22.2 950 FDA

FCC Part 15 subpart B class B,

CSA C108.8 class B

AS/NZS 3548 class B

Electrical Requirements

Voltage AC 110 – 120 V Frequency 50 – 60 Hz Current 0.6 A/110 – 120 V

Power consumption

Printing Approx. 21 W Sleep mode Approx. 3.5 W

ENERGY STAR® qualified (Tier 2)

Acoustic Noise Level

Approximately 39 dB according to ISO 7779

Printer Language/Drivers

Epson ESC/P®2 raster photographic drivers standard

Weight/Dimensions

Printer weight 27.5 lb

Dimensions 24.5" (W) x 12.8" (D) x 8.6" (H)

Connectivity

Hi-Speed USB 2.0 (1 port) 100Base-T Ethernet (1 port) Wi-Fi CERTIFIED (802.11n only) PictBridge™ (1 port)

Operating Systems Supported

Mac® Mac OS® X 10.5.x – 10.6.x Windows Windows® 7 (32-bit, 64-bit), Windows Vista® (32-bit, 64-bit),

Windows XP, Windows XP Professional x64 Edition

Product	Part Numbe
Epson Stylus Photo R2000 printer	C11CB35201
Epson Stylus Photo R2000 printer (Canada)	C11CB35211

Extended Service Programs

1-year Extended Service Plan EPPSNVIJE1 2-year Extended Service Plan EPPSNVIJE2

Epson UltraChrome Hi-Gloss 2 Ink^B


159 Photo Black ink cartridge	T159120
159 Cyan ink cartridge	T159220
159 Magenta ink cartridge	T159320
159 Yellow ink cartridge	T159420
159 Red ink cartridge	T159720
159 Matte Black ink cartridge	T159820
159 Orange ink cartridge	T159920
159 Gloss Optimizer cartridges (2)	T159020

- Compared to the Epson Stylus Photo R1900.
- †† Not recommended for Wi-Fi 802.11 b/g. Level of performance subject to the range of the router being used. Visit www.wi-fi.org/files/11nbasics_glossary.pdf, under Range, for more information.
- A Color photo speed in SuperFine Mode on Premium Photo Paper Glossy measured from start of paper feed. Actual print time will vary based on system configuration, software application and page complexity.
- B Cartridge yields vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink color. A variable amount of ink remains in the cartridge after the "replace cartridge" signal. Part of the ink from the first cartridges is used for printing the printer. Ink is used for both printing and print head maintenance. All inks are used for both black and color printing, and all colors have to be installed for printing. For more information about cartridges, see www.epson.com/cartridgeinfo

www.epson.com/R2000 www.epson.ca/R2000

Better Products for a Better Future™

eco.epson.com





Epson America, Inc.: 3840 Kilroy Airport Way, Long Beach, CA 90806 Epson Canada Limited: 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com | www.epson.ca



















EPSON ULTRACHROME Hi-Gloss* 2 Ink



ACCUPHOTO HG

Specifications and terms are subject to change without notice. Epson, Epson ESC/P, Epson Stylus, Epson UltraChrome Hi-Gloss and MicroPiezo are registered trademarks, Epson Exceed Your Vision is a registered logomark and Better Houtes for a Better Future is a trademark of Seiko Epson Corporation. Borderfree and UltraSmooth are registered trademarks and AccuPhoto, AMC and PreciseColor are trademarks of Epson America, Inc. Microsoft, Windows, Windows Vista and the Windows logos are trademarks of the Microsoft group of companies. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2011, Epson America, Inc. CPD-34156 XWK 5/11 XX