

KODAK PROFESSIONAL EKTAR 100 Film

Kodak alaris

TECHNICAL DATA / COLOR NEGATIVE FILM


January 2025 • E-4046

KODAK PROFESSIONAL EKTAR 100 Film is the world's finest grain color negative film. With ISO 100 speed, high saturation and ultra-vivid color, this film offers the finest, smoothest grain of any color negative film available today. An ideal choice for commercial photographers and advanced amateurs, KODAK PROFESSIONAL EKTAR 100 Film is recommended for applications such as nature, travel and outdoor photography, as well as for fashion and product photography.

| TECHNOLOGY | BENEFIT |
|---|---|
| <ul style="list-style-type: none">Incorporates Entertainment Imaging's KODAK VISION Film technologyMicro-Structure Optimized KODAK T-GRAIN EmulsionsKODAK Proprietary Advanced Development Accelerators | <ul style="list-style-type: none">World's finest-grained color negative filmIdeal for scanningExtraordinary enlargement capability from a 35mm negative |
| <ul style="list-style-type: none">Optimized Emulsion Spectral Sensitivity and Image Modifier Chemistry | <ul style="list-style-type: none">Ultra-vivid color |
| <ul style="list-style-type: none">KODAK Advanced Cubic EmulsionsKODAK Proprietary DIR Couplers | <ul style="list-style-type: none">Optimized sharpnessDistinct edges, fine detail |
| <ul style="list-style-type: none">Unified Emulsion Technology | <ul style="list-style-type: none">Printing compatible with other KODAK Films |

SIZES AVAILABLE

Availability may differ from country to country. See your dealer who supplies KODAK PROFESSIONAL Products.

| Size/Format | Notch Code | Base |
|-------------|---|--|
| 135 | N/A | 0.10 mm (3.94 mil) ESTAR Thick Base |
| 120 | N/A | 0.10 mm (3.94 mil) ESTAR Thick Base |
| Sheets |  | 0.19 mm (7.5 mil) ESTAR Thick Base |

STORAGE AND HANDLING

Store unexposed film at 21°C (70°F) or lower in the original sealed package. For extended periods, store film at 13°C (55°F) to preserve consistency.

To avoid moisture condensation on film that has been refrigerated, allow the film to warm up to room temperature before opening the package. Typical warm-up times are given in the table below.

| Size | Warm-Up Times (Hours) to Reach Room Temperature of 21°C (70°F) From a Storage Temperature of: | | |
|--------------|---|------------|-------------|
| | -18°C (0°F) | 2°C (35°F) | 13°C (55°F) |
| 135 magazine | 1½ | 1¼ | 1 |
| 120 | 1 | ¾ | ½ |
| 10-sheet box | 1½ | 1 | 1 |

Load and unload roll-film cameras in subdued light. Total darkness is required when you load and unload sheet film holders.

Process film as soon as possible after exposure. Protect negatives from strong light, and store them in a cool, dry place. For long-term storage, keep negatives at a temperature between 2°C (35°F) and 13°C (55°F) and at a relative humidity between 30 and 35 percent.

DARKROOM RECOMMENDATIONS

Do not use a safelight. Handle unprocessed film in total darkness.

EXPOSURE

Film Speed

Use the speed numbers in the tables below with cameras or meters marked for ISO, ASA, or DIN speeds or exposure indexes (EIs). Do not change the film-speed setting when metering through a filter. Metering through filters may affect light meter accuracy; see your meter or camera manual for specific information. For critical work, make a series of test exposures.

| Light Source | KODAK WRATTEN Gelatin Filter | ISO Speed |
|------------------------------|------------------------------|-----------|
| Daylight or Electronic Flash | None | 100 |
| Photolamp (3400 K) | No. 80B | 32 |
| Tungsten (3200 K) | No. 80A | 25 |

* For best results without special printing.

Daylight

Use the exposures in the table below for average frontlit subjects from 2 hours after sunrise to 2 hours before sunset.

| Lighting Conditions | Shutter Speed (second) and Lens Opening |
|--|--|
| Bright or Hazy Sun on Light Sand or Snow | 1/125 f/16 |
| Bright or Hazy Sun (Distinct Shadows) | 1/125 f/11* |
| Weak, Hazy Sun (Soft Shadows) | 1/125 f/8 |
| Cloudy Bright (No Shadows) | 1/125 f/5.6 |
| Heavy Overcast or Open Shade‡ | 1/125 f/4 |

* Use f/5.6 for backlit close-up subjects.
† Use f/8 for backlit close-up subjects.
‡ Subject shaded from the sun but lighted by a large area of sky.

Adjustments for Long and Short Exposures

No filter correction or exposure compensation is required for exposures from 1/10,000 second to 1 second. For critical applications with longer exposure times, make tests under your conditions.

Electronic Flash

Use the appropriate guide number in the table below as starting-point recommendations for your equipment. Select the unit output closest to the number given by your flash manufacturer. Then find the guide number for feet or metres. To determine the lens opening, divide the guide number by the flash-to-subject distance. If negatives are consistently too dense (overexposed), use a higher guide number; if they are too thin (underexposed), use a lower number.

| Unit Output (BCPS)* | Guide Number Distances in Feet/Metres |
|---------------------|--|
| 350 | 40/12 |
| 500 | 50/15 |
| 700 | 60/18 |
| 1000 | 70/21 |
| 1400 | 85/26 |
| 2000 | 100/30 |
| 2800 | 120/36 |
| 4000 | 140/42 |
| 5600 | 170/50 |
| 8000 | 200/60 |

* BCPS = beam candlepower seconds

Fluorescent and High-Intensity Discharge Lamps

Use the color-compensating filters and exposure adjustments in the tables below as starting points to expose KODAK PROFESSIONAL EKTAR 100 Film under fluorescent or high-intensity discharge lamps. For critical applications, make a series of test exposures under your actual conditions.

To avoid the brightness and color variations that occur during a single alternating-current cycle, use exposure times of 1/60 second or longer with fluorescent lamps; with high-intensity discharge lamps, use exposure times of 1/125 second or longer.

| Type of Fluorescent Lamp | KODAK Color Compensating Filter(s) | Exposure Adjustment |
|--------------------------|------------------------------------|---------------------|
| Daylight | 20R + 5M | +1 stop |
| White | 40B + 5C | +1 2/3 stop |
| Warm White | 40B + 40C | +2 stops |
| Warm White Deluxe | 40B + 50C | +2 stops |
| Cool White | 30B | +1 stop |
| Cool White Deluxe | 40C + 10M | +1 stop |

| High-Intensity Discharge Lamp (CCT) | KODAK Color Compensating Filter(s) | Exposure Adjustment |
|-------------------------------------|------------------------------------|---------------------|
| High-Pressure Sodium Vapor | 50B + 70C | +2 2/3 stops |
| Metal Halide | 5C + 10M | +2/3 stop |
| Mercury Vapor with Phosphor | 30B + 5C | +1 stop |
| Mercury Vapor without Phosphor | 80R | +1 2/3 stop |

PROCESSING

Process EKTAR 100 Film in KODAK FLEXICOLOR Chemicals for Process C-41 using the replenishment and wash rates in the tables below. Note that the developer replenishment rates are starting-point recommendations only and may vary due to the amount of exposure to the film, scene content, and the presence/absence of sprocket holes.

Replenishment and Wash Rates

| Film Size | KODAK FLEXICOLOR Developer Replenisher | KODAK FLEXICOLOR Developer Replenisher LORR | KODAK FLEXICOLOR Bleach III, Fixer, and Stabilizer | Wash Water* |
|-----------|---|--|--|--|
| 135 | 1012 mL/m ² 94 mL/ft ² | 506 mL/m ² 47 mL/ft ² | 861 mL/m ² 80 mL/ft ² | 31 L/m ² 2.9 L/ft ² |
| 120 | 1012 mL/m ² 94 mL/ft ² | 506 mL/m ² 47 mL/ft ² | 1023 mL/m ² 107 mL/ft ² | 31 L/m ² 2.9 L/ft ² |
| 4 x 5 | 1012 mL/m ² 94 mL/ft ² | 506 mL/m ² 47 mL/ft ² | 1023 mL/m ² 107 mL/ft ² | 31 L/m ² 2.9 L/ft ² |
| 8 x 10 | 1012 mL/m ² 94 mL/ft ² | 506 mL/m ² 47 mL/ft ² | 1023 mL/m ² 107 mL/ft ² | 31 L/m ² 2.9 L/ft ² |

* Rates are for first wash and a two-stage countercurrent final wash. Double these rates for a single stage final wash.

JUDGING NEGATIVE EXPOSURES

You can check the exposure level with a suitable electronic densitometer equipped with a filter such as a KODAK WRATTEN Gelatin Filter No. 92 or the red filter for Status M densitometry. Depending on the subject and the light source used for exposure, a normally exposed and processed color negative measured through the red filter should have the approximate densities listed below.

Because of the extreme range in skin color, use these red density values for a normally lit forehead only as a guide. For best results, use a KODAK Gray Card (gray side).

| Area Measured | Density Reading |
|--|------------------------------|
| KODAK Gray Card (gray side) receiving same illumination as subject | 0.77 to 0.87 |
| Lightest step (darkest in the negative) of a KODAK Paper Gray Scale receiving same illumination as subject | 1.13 to 1.23 |
| Highest diffuse density on normally lighted forehead —light complexion —dark complexion | 1.08 to 1.18 0.93 to 1.03 |

PRINTING NEGATIVES

This film is optimized for printing to —

KODAK PROFESSIONAL ENDURA Premier Paper

KODAK PROFESSIONAL ENDURA Premier Canvas Paper

KODAK PROFESSIONAL ENDURA Premier Metallic Paper

KODAK PROFESSIONAL ENDURA Transparency Display Material

KODAK PROFESSIONAL ENDURA Clear Display Material

SCANNING NEGATIVES

You can easily scan EKTAR 100 Film negatives with a variety of linear-array-CCD, area-array-CCD, and PMT film scanners. You can scan negatives on desktop scanners as well as high-end drum scanners.

IMAGE STRUCTURE

Print Grain Index

The Print Grain Index number refers to a method of defining graininess in a print made with diffuse-printing illumination. It replaces rms granularity and has a different scale which cannot be compared to rms granularity.

- The method uses a uniform perceptual scale, with a change of four units equaling a just noticeable difference in graininess to 90 percent of observers.
- A Print Grain Index rating of 25 on the scale represents the approximate visual threshold for graininess. A higher number indicates an increase in the amount of graininess observed.
- The standardized inspection (print-to-viewer) distance for all print sizes is 14 inches, the typical viewing distance for a 4 x 6-inch print.
- In practice, larger prints will likely be viewed from distances greater than 14 inches, which reduces apparent graininess.
- Print Grain Index numbers may not represent graininess observed from more specular printing illuminants, such as condenser enlargers.

Negative Size: 24 x 36 mm (135)

| | | | |
|----------------------|---------------|------|-------|
| Print Size in inches | 4x6 | 8x10 | 16x20 |
| Magnification | 4.4X | 8.8X | 17.8X |
| Print Grain Index | less than 25* | 38 | 66 |

* 25 is the visual threshold for perception of grain.

Negative Size: 6 x 6 cm (120)

| | | | |
|----------------------|--------------|--------------|-------|
| Print Size in inches | 4x6 | 8x10 | 16x20 |
| Magnification | 2.6X | 4.4X | 8.8X |
| Print Grain Index | less than 25 | less than 25 | 38 |

Negative Size: 4 x 5 Inches (Sheets)

| | | | |
|----------------------|--------------|--------------|--------------|
| Print Size in inches | 4x6 | 8x10 | 16x20 |
| Magnification | 1.2X | 4X | 8X |
| Print Grain Index | less than 25 | less than 25 | less than 25 |


Negative Size: 8 x 10 Inches (Sheets)

| | | | |
|----------------------|--------------|--------------|--------------|
| Print Size in inches | 4x6 | 8x10 | 16x20 |
| Magnification | 0.6X | 1X | 2X |
| Print Grain Index | less than 25 | less than 25 | less than 25 |


KODAK PROFESSIONAL EKTAR 100 Film

CURVES


Characteristic Curves




Spectral-Dye-Density Curves



Spectral-Sensitivity Curves



Modulation Transfer Function



© 2025 Kodak Alaris Inc.
TM: Endura, Flexicolor and Portra
The Kodak, Kodak Professional, Ektar, Estar, T-Grain, Vision, and Wratten trademarks are used under license from Eastman Kodak Company.

Revised 1/25

KODAK PROFESSIONAL EKTAR 100 Film
KODAK Publication No. E-4046