

PRODUCT LAUNCH

SPECIFICATIONS:

Type	Half-frame behind-the-lens shutter 35mm film camera
Frame Size	24×17mm
Compatible Film	35mm film: ISO 50, ISO 100, ISO 125, ISO 160, ISO 200, ISO 400, ISO 800, ISO 1600, ISO 3200
Sensitivity Setting	Manual settings to match the film
Film Loading	Easy loading
Film Advance	Manual winding using wind-up lever (with 130-degree stroke and 35-degree stand-off angle)
Film Rewind	Manual rewinding using rewind crank. Mid-roll rewinding possible.

Lens

Lens	HD PENTAX Lens
Focal Length	25mm (equivalent to 37mm in 35mm format)
Maximum Aperture	F3.5
Lens Configuration	3 elements in 3 groups
Angle of View (Diagonal)	61°
Maximum Magnification	Approx. 0.13x (at 0.25m)
Filter Diameter	ø40.5mm

Viewfinder

Type	Albada bright-frame viewfinder
Viewfinder Indication	Composition frame, Close-distance composition frame Zone focusing setting can be confirmed through the viewfinder
Viewfinder Outer Right	Blue lamp display: Warning display, Orange lamp display: Flash display

Focusing

Type	Zone-focusing (Manual operation)
Switchover Distance	6 zones (0.25m, 0.5m, 1.2m, 1.7m, 3m, ∞) (0.82ft, 1.7ft, 4ft, 5.6ft, 10ft, ∞)

Exposure Control

Metering Type	Partial metering
Metering Range	EV2.5 to 16.5 (ISO100)
Exposure Compensation	±2EV (1/3EV steps)
Shooting Mode (Exposure)	Full auto (Pan focus program AE, Auto flash), Standard (Program AE, Flash off), Slow-speed shutter (Slow-speed program AE, Flash off), Maximum aperture priority (Maximum aperture priority program AE, Flash off), Bulb (Bulb, Flash off), Daylight sync (Program AE, Flash on), Slow-speed sync (Slow-speed program AE, Flash on)

Shutter

Type	Program AE electronic shutter
Shutter Speed	1/350 to 4 seconds, Bulb

Flash

Built-in Flash	Guide Number approx.6 (ISO100 · m)
Emission Type	Shooting mode interlocking system
Flash Charging Time	Approx. 9 seconds
Charging Status	Can be checked with the orange lamp at viewfinder outer right. Charging status: blinking Charging completion status: lighting

Power Source

Battery Type	One 3V lithium battery (CR2), Not compatible with rechargeable CR2 type batteries
Battery Life	Approx. 10 cartridges* when using 36 exposure film (using fresh battery under the condition of 50% flash shots) * According to the result of RICOH IMAGING in-house testing.

External Terminal

Cable Switch Terminal	Compatible with cable switch CS-205 (optional) (ø2.5mm)
-----------------------	---